Fax to: +49 (0)3328/437-444

UP200St – A Powerful and Robust 200 Watts Ultrasonic Device for Lab and Small Scale Production

www.hielscher.com/up200st

Ultrasonic Device **UP200St**



UP200St – digital homogenizer with acrylic sound protection box



UP200St for stamdmounted and hand-held use

Technical Details

UP200St: 200 watts, 26kHz; for handheld and stand-mounted use; seperated generator and transducer (UP200St-T + UP200St-G) fulfilling IP51 + IP65 grade, automatic frequency tuning, amplitude adjustable from 20 to 100%, pulse adjustable from 0 to 100%, with colored touch-screen & digital control, operation and control via LAN, automatic data recording, dry running protected, titanium horn \emptyset 14mm, amplitude at horn 70µm, in portable case

Applications

Homogenization, Dispersing & Deagglomeration (e.g. nano particles), Emulsifying, Lysis & Cell Disintegration, Extraction, Degassing, Sonochemistry & Sono-Catalysis

Advantages

Performance: 200 watts power, very reliable & robust device for heavy duty operation

Flexibility: Handheld or stand-mounted use, with various accessories for optimal adaption to your process.

Comfortable Operation: The separated design of transducer and generator allows to place the generator safely outside the operation area.. The operation settings can be adjusted via the colored touch-screen. All functions are intuitively reachable through one main menu. **Quality**: The UP200St device fullfills the highest quality standards. All devices are designed, engineered and manufactured in Germany.

Items:

- ☐ Ultrasonic Device UP200St (generator + transducer)
- ☐ Sonotrode S26d2 (tip diameter 2mm)
- ☐ Sonotrode S26d7 (tip diameter 7mm)
- ☐ Sonotrode S26d14 (tip diameter 14mm)
- ☐ Stand ST1-16
- ☐ Sound Protection Box SPB-L, made from acryl glass

